TYPE 600 FORGED BRASS, BALL VALVES

KITZ Fig: AKSZA

Sizes: 1/4-4inch(8-100mm)

Standards

End to End: KITZ STANDARDEnd Connection: ASME B1.20.1Wall Thickness: KITZ STANDARD

Test Standard
. KITZ STANDARD

Dimensions

2 1 1110110 1 0110						
SIZE(incl	n/mm)	L	L1	Н	D1	Kg
1/4	8	42.0	0.0	37.0	70.0	0.00
3/8	10	42.0	0.0	37.0	70.0	0.00
1/2	15	53.0	0.0	40.0	80.0	0.00
3/4	20	60.0	0.0	44.0	80.0	0.00
1	25	72.0	0.0	50.0	110.0	0.00
11/4	32	84.0	0.0	55.0	110.0	0.00
11/2	40	92.0	0.0	65.0	150.0	0.00
2	50	110.0	0.0	72.0	150.0	0.00
21/2	65	5.4	0.0	4.0	7.9	0.00
3	80	6.6	0.0	4.4	11.8	0.00
4	100	7.6	0.0	5.2	11.8	0.00

Material List

Material List			
NAME OF PART	MATERIAL	SPECIFICATION	
BODY	FORGED BRASS	C3771	
BODY CAP	FORGED BRASS	C3771	
STEM	BRASS ROD (2)	C3604(5)	
BALL	STAINLESS STEEL	SCS13A	


Specifications

TYPE 600 FORGED BRASS, BALL VALVES

End to End: KITZ STANDARD, End Connection: ASME B1.20.1, Wall Tchickness: KITZ STANDARD, Test Standard: KITZ STANDARD, Sizes: 1/4-4inch(8-100mm), BODYMATERIAL: FORGED BRASS, BODY CAPMATERIAL: FORGED BRASS, STEMMATERIAL: STAINLESS

STEEL, KITZ Fig: AKSZA





For more details, please refer to the drawing. -

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



